

manual motor starters		single phase motor												
Types	Adustable Current range(A)	Rated capacity (HP) 110-120V	rated operational current(A)	Rated capacity (HP) 200V	rated operational current(A)	Rated capacity (HP) 208V	rated operational current(A)	Rated capacity (HP) 220-240V	rated operational current(A)	Rated capacity (HP) 440-480V	rated operational current(A)	Rated capacity (HP) 550-600V	rated operational current(A)	
BM3VHB	-010	6.3-10	1/3	7.2	3/4	7.9	3/4	7.6	3/4	6.9	3	8.5	3	6.8
	-013	9-13	1/2	9.8	1	9	1	8.8	1-1/2	10				
	-016	11-16	3/4	13.8	1-1/2	12	1-1/2	11	2	12	5	14	5	11
	-020	14-20	1	16.0	2	14	2	13						
	-025	19-25	1-1/2	20	3	19.6	3	19	3	17			7-1/2	16
	-032	24-32	2	24			5	31	5	28	7-1/2	21	10	20
	-040	28-40	3	34	5	32.2			5	28	10	26	15	27
	-050	35-50			7-1/2	46	7-1/2	44	7-1/2	40	15	34	20	35
-063	45-63	5	56	10	57.5	10	55	10	50	20	44	25	44	
										25	55	30	54	

