

## (5) Molded Case Circuit Breakers

### ● Mainframe of MCCBs

Series	AF	2-poles	3-poles	Rated breaking current (Icu/lcs) [kA] <sup>*1</sup>			Certificate No.
				Ue: 230V AC	Ue : 400V AC	Ue: 440V AC	
E	30	EA32AC	EA33AC	2.5/2	1.5/1	1.5/1	2003010307063433
	50	EA52AC	EA53AC	2.5/2	1.5/1	1.5/1	2003010307063433
		EA52C	EA53C	5/3	2.5/2	2.5/2	2003010307063635
	60	EA62C	EA63C	5/3	2.5/2	2.5/2	2003010307063385
	100	-	EA103AC	5/3	1.5/1	-	2003010307063440
		EA102C	EA103C	25/13	10/5	10/5	2003010307063647
	225	EA202C	EA203C	35/18	15/4	-	2004010307116273
		-	EA203CM	35/18	15/4	-	2004010307116273
400	EA402C	EA403C	35/18	25/13	-	Available in Jan. 2005	
600	-	EA603C	50/25	35/18	-	Available in Jan. 2005	
800	-	EA803C	50/25	35/18	-	Available in Jan. 2005	
S	30	SA32C	SA33C	5/3	2.5/2	2.5/2	2003010307063635
	50	SA52C	SA53C	10/5	7.5/4	7.5/4	2003010307063640
		SA52RC	SA53RC	25/13	10/5	10/5	2003010307063643
	60	SA62C	SA63C	10/5	7.5/4	7.5/4	2003010307063646
		SA62RC	SA63RC	25/13	10/5	10/5	2003010307063647
	100	SA102C	SA103C	50/25	25/7	-	2004010307116286
		-	SA103CM	50/25	25/7	-	2004010307116286
		SA102RC	SA103RC	100/50	50/13	-	2004010307116288
		-	SA103RCM	100/50	50/13	-	2004010307116288
	225	SA202C	SA203C	50/25	25/7	-	2004010307116280
		-	SA203CM	50/25	25/7	-	2004010307116280
		SA202RC	SA203RC	100/50	50/13	-	2004010307116280
		-	SA203RCM	100/50	50/13	-	2004010307116280
400	SA402C	SA403C	50/25	35/18	-	Available in Jan. 2005	
	SA402RC	SA403RC	85/43	50/25	-	Available in Jan. 2005	
600	-	SA603RC	85/43	50/25	-	Available in Jan. 2005	
800	-	SA803RC	85/43	50/25	-	Available in Jan. 2005	

\*1 For rated breaking current and rated voltage, the values in this table are approved.