

Short circuit capability and SCSOA

Small IPM X series P642 Package

A short circuit capability dependency on control circuit voltage V_{CC} is shown in the document. Conditions: $V_{P-N(*)}=400V$, $T_{vi}=125^{\circ}C$, non-repetitive pulse

The definition of short circuit current I_{SC} and short circuit capability t_{SC} are shown in Fig.1. In the case of 6MBP50XTA065-50, the IGBT can be safely shut down with t_{SC} less than 5.1µs at $V_{CCL}=V_{CCH}=V_{B(*)}=16.5V$, and the I_{SC} is 7 times the rated current. The SCSOA varies depending on the input voltage V_{DC} , control voltage V_{CC} , junction temperature T_{vj} , etc. Please be careful to design with a suitable margin. Each page shows data for each product.




Fig.1 Definition of I_{SC} and t_{SC}

Type name: 6MBP50XTA065-50, 6MBP50XTC065-50




Fig.2 6MBP50XTA(C)065-50 Short circuit capability and SCSOA



Type name : 6MBP75XTA065-50, 6MBP75XTC065-50




Fig.5 6MBP75XTA(C)065-50 Short circuit capability and SCSOA



WARNING

- 1. This Catalog contains the product specifications, characteristics, data, materials, and structures as of May 2023. The contents are subject to change without notice for specification changes or other reason. When using a product listed in this Catalog, be sure to obtain the latest specifications.
- 2. All applications described in this Catalog exemplify the use of Fuji's products for your reference only. No right or license, either express or implied, under any patent, copyright, trade secret or other intellectual property right owned by Fuji Electric Co., Ltd. is (or shall be deemed) granted. Fuji Electric Co., Ltd. makes no representation or warranty, whether express or implied, relating to the infringement or alleged infringement of other's intellectual property rights which may arise from the use of the applications described herein.
- 3. Although Fuji Electric Co., Ltd. is enhancing product quality and reliability, a small percentage of semiconductor products may become faulty. When using Fuji Electric semiconductor products in your equipment, you are requested to take adequate safety to prevent the equipment from causing a physical injury, fire, or other problem if any of the products become faulty. It is recommended to make your design failsafe, flame retardant, and free of malfunction.
- 4. The products introduced in this Catalog are intended for use in the following electronic and electrical equipment which has normal reliability requirements.
 - Computers · ÓA equipment · Communications equipment (terminal devices) · Measurement equipment
 - Machine tools · Audiovisual equipment · Electrical home appliances · Personal equipment · Industrial robots etc
- 5. If you need to use a product in this Catalog for equipment requiring higher reliability than normal, such as for the equipment listed below, it is imperative to contact Fuji Electric Co., Ltd. to obtain prior approval. When using these products for such equipment, take adequate measures such as a backup system to prevent the equipment from malfunctioning even if a Fuji's product incorporated in the equipment becomes faulty.
 - Transportation equipment (mounted on cars and ships)
 Trunk communications equipment
 - Traffic-signal control equipment
 Gas leakage detectors with an auto-shut-off feature
 - Emergency equipment for responding to disasters and anti-burglary devices
 Safety devices
 - · Medical equipment.
- 6. Do not use products in this Catalog for the equipment requiring strict reliability such as the following and equivalents to strategic equipment (without limitation).
 - Space equipment · Aeronautic equipment · Nuclear control equipment · Submarine repeater equipment
- 7. All rights reserved. No part of this Catalog may be reproduced without permission in writing from Fuji Electric Co., Ltd.
- If you have any question about any portion in this Catalog, ask Fuji Electric Co., Ltd. or its sales agents before using the product. Neither Fuji Electric Co., Ltd. nor its agents shall be liable for any injury caused by any use of the products not in accordance with instructions set forth herein.